

CAT 6, Class E Keystone Module, unshielded 0880.H6U1SH



✓ Category 6, ClassE

✓ Unshielded

✓ RJ45 jack

✓ Cable entry: Rear side

Abstract

CAT 6, Class E Keystone Module, unshielded, toolfree installation

Features

- Cable entry: Rear side
- Material housing: Abs halogen free, UL 94 V0
- Contacts: Phosphor, bronze
- Coating of contacts: Nickel, gold plated 0.6 µ
- Operating temperature: -10 °C bis +50 °C
- Material circuit board: FR4, 1.2 mm
- Mating cycles: ≥ 750
- RJ45 outlet for mounting in Patch Panel
- IDC contacts: Phosphor, bronze
- Layer: 50 µm gold over 40 µm nickel
- Cable connection type: Tool free with cable hatch for strong/flexible conductions AWG 23-26
- Wiring standard: EIA/TIA 568 A/B
- Conformity: Category 6 / 1GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002
- Dimensions: 35x25x17 mm
- Weight: ca. 12 g
- Compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels
- Opening dimensions according to Keystone standard 19.35x14.8 mm

Product Overview

The Item "H6U1SH" is an unshielded Keystone Module with tool free installation which provides best performance and link quality for your network. The compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels It is conform to Category 6 / 1GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002 and certificated by GHMT.

Product Number Information

H6U1SH CAT 6 Keystone Module, unshielded, RJ45 to LSA, toolfree installation, incl. cable tie

Product Images



Technical Drawings

